





V2VENTS.COM (916) 652-7424 info@newcalmetals.com P.O. Box 1126 Loomis, CA. 95650


**For use to comply with IWUI, IBHS Wildfire Prepared Certification, California Chapter 7A\***



**End View**




\* Low profile, hinged assembly for easy inspections.




**Isometric View**

For use to comply with SB 721, SB 326 where decks and balconies (EEE) require inspection. Vulcan Vents have been tested and listed to ASTM E2886 and carry a 1 hour fire rating listed by ICC. All NFVA have been verified by ICC's engineering division.


A	B	C	NFVA
4"	24"	6"	39 SI
4"	36"	6"	58 SI
4"	48"	6"	77 SI
4"	60"	6"	96 SI
4"	72"	6"	115 SI
4"	120"	6"	192 SI



**Top View**



Quick, secure access.



**Bottom View**

**Required Installation:**

Use **EverKem 814+ intumescent firestop caulking** or equivalent, BEHIND flanges. For application details and installation examples, please visit [www.V2Vents.com](http://www.V2Vents.com)

\* Door is interchangeable with our non-fire rated vent option.

Proudly Manufactured By: NEW CAL METALS INC.

[www.newcalmetals.com](http://www.newcalmetals.com)

**FSVSC4120IF PRODUCT SPECIFICATION & DATA SHEET**

Model Description | **Continuous**  
Model Number | **FSVSC4120IF**  
Model Size | **120" x 4"**

Flange Type | **Inspection**  
NFVA | **192 sq. in.**

Frame & Flange | **G90 Galvanized Steel - 24GA**  
Intumescent Core | **5mm Hexagonal Matrix - Aluminum with intumescent coating**  
Ember Mesh | **14 Mesh - 304 Stainless Steel (Faces interior)**